



# COR VISION PLUS SLIDING SYSTEM

TBB

## ENERGY EFFICIENCY

Thermal Transmission Coefficient

**$U_w \geq 0.9$  (W/m<sup>2</sup>K)**

Please consult typology, dimensions and glazing

## ACCOUSTIC INSULATION

Maximum glazing: **56 mm**

Maximum acoustic insulation: **Rw = 43 dB**

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12207):

**Class 4**

Water tightness (EN 12208):

**Class 7A\* / 9A\***

Wind resistance (EN 12210):

**Class C3\* / C4\*\***

\* Reference test balcony 4.00 x 3.00 m / 2 sashes

\*\* Reference test balcony 4.00 x 3.00 m / 1 sash + 1 fixed light

<b>SECTIONS</b>	Frame 180 mm / 278 mm 3 Rails Sash 69 mm	<b>EXTRUSION ALLOY</b>	6063 T-5
<b>PROFILE THICKNESS</b>	Door 2.0 mm	<b>POLYAMIDE STRIP LENGTH</b>	Frame 40 mm Sash 18 / 32 mm
<b>MAXIMUM DIMENSIONS</b>	Width (L) = 4.000 mm Height (H) = 4.000 mm <small>*Glazed surface 14 m</small>	<b>OPENING POSSIBILITIES</b>	Sliding 1, 2, 3, and 4 sashes Possibility of interior and exterior corner sash at 90° without mullion Galandage
<b>MAXIMUM WEIGHT/SASH</b>	400 kg Manual 700 Kg Motorized		

Please consult regarding maximum weight and dimensions according to types

## FINISHES

Colour powder coating  
(RAL, mottled, rough...)

According to Qualicoat >60 micras

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras

Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured

